

## 19" Rack Mount

- Accommodates 12 Core Tec Modules (Rear Mount)
- Redundant power supply optional (Hot Swappable w/ load sharing, Auto Power Transfer, etc.)
- Extended Temperature Range (-20°C - +70°C)
- 4RU (6.9" high)
- 86-254 VAC input power
- On/Off power switch
- Cover Plates for empty slots available
- Combines MPEG2, MPEG4, H.264, H.264/MPEG2/4/J Encoders and/or H.264, MPEG2, MPEG4, H.264/MPEG2/4/J Decoders in the same chassis



## Enclosure

<b>Dimensions</b>	19" W x 15"L x 6.9" H	
<b>Weight</b>	Enclosure Only	13.8 lbs.
	w/ Single Power Supply	16.6 lbs.
	w. Dual Power Supply	19.4 lbs.

## Card Cage

Module Slots	12
Slot Width	0.93"
Material	.125" Al

## Power Supply (for each power supply)

Input Voltage	85-264 VAC/47-63 HZ
DC Output Voltage	12 Volts
Rated Output Current	16.7 Amps
Rated Output Power	200 Watts
AC Current	2.8A@115VAC/1.4A@230VAC
Inrush Current	40A @ 230 VAC
Line Regulation	0.50%
Load Regulation	0.50%
Operating Temp.	(-)20°C to +70°C
(Output De-Rated 60% @ 60C, 50% @ 70C)	

## Compatible Cards (\* 10/100 Ethernet Interface)

- VCX-2400-E-R MPEG2 Encoder\*
- VCX-2401-E-R MPEG2 Encoder\*
- VCX-2400-D-R MPEG2 Decoder\*
- VCX-2401-D-R MPEG2 Decoder\*
- VCX-4400-E-R MPEG4 Encoder\*
- VCX-4401-E-R MPEG4 Encoder\*
- VCX-4402-E-R MPEG4 Encoder\*
- VCX-4400-D-R MPEG4 Decoder\*
- VCX-4401-D-R MPEG4 Decoder\*
- VCX-4402-D-R MPEG4 Decoder\*
- VCX-6400-E-R MPEG2/4/J Encoder\*
- VCX-6400-D-R MPEG2/4/J Decoder\*
- VCX-7401-E-R H264/MPEG2/4/J Encoder\*

## Regulatory Approvals

North America	FCC Title 47 Subpart B, Section 15, Class A
---------------	--

## Ordering Information

R-12	Card Cage Chassis
R-12-PS	Stand Alone Power Supply
R-12-NPS	Card Cage/No Power Supply
R-12-DPS	Card Cage/Dual Power Supply